

“ITD Blockout” aka “in the dark”

Inherently flame retarded block-out fabric

rev 0 June 2008

Specification:

Composition:	100% modified polyester – triple weave
Flame retardant:	inherently flame retarded
Width:	150 cm
Weight:	261gsm
Pieces:	Approx. 50 m

Testing:

AS 1530.2-1993 Test for Flammability of Materials
Flammability Index: 2

AS 1530.3-1999 Simultaneous Determination of Ignitability,
Flame Propagation, Heat Release and Smoke Release
Ignitability Index: 0
Spread of Flame Index: 0
Heat Evolved Index: 0
Smoke Developed Index: 0-1

Light Reduction:

Base cloth (natural light grey)	approx. 80%
Transfer printed (colour dependant)	approx. 80%+
Dyed Black	approx. 95%

Handling and Maintenance:

Anticipated fabric life 20 to 25 years (general figure only, environmental factors such as UV light exposure, humidity and traffic may further reduce useful life of fabric).

Flame retardant inherently flame retarded, not effected by water.

Cleaning: Regular vacuuming recommended.
Depending on curtain construction - dry clean or commercial
launder – treat as polyester. Carefully fold and re-hang ASAP to
avoid creasing which may be difficult to remove.

Spot Cleaning: warm water and low/non-alkaline detergent, as per
manufacturer’s instructions. Test on a concealed area of fabric
before proceeding.